

1. A method of forming a security article, comprising the steps of:

1 providing a light transmissive substrate having a first surface and an opposing
2 second surface, the first surface having an optical interference pattern; and

3 forming a color shifting optical coating on the second surface of the substrate,
4 the optical coating providing an observable color shift as the angle of incident light or
5 viewing angle changes.
6

7
8 2. The method of claim 1, wherein the optical interference pattern is formed by
9 embossing a diffraction grating pattern or a holographic image pattern on the first surface of
10 the substrate.
11

12
13 3. The method of claim 1, wherein the color shifting optical coating is formed by
14 depositing an absorber layer on the second surface of the substrate, depositing a dielectric
15 layer overlying the absorber layer and depositing a reflector layer overlying the dielectric
16 layer.
17

18
19 4. The method of claim 1, wherein the color shifting optical coating is formed by
20 depositing a first absorber layer on the second surface of the substrate, depositing a dielectric
21 layer overlying the absorber layer and depositing a second absorber layer overlying the
22 dielectric layer.
23
24
25
26

1 5. The method of claim 1, wherein the color shifting optical coating is formed by
2 applying a color shifting ink comprising a plurality of multilayer color shifting flakes
3 dispersed in a polymeric medium to the second surface of the substrate.
4

5 6. The method of claim 1, wherein the color shifting optical coating is formed on the
6 second surface of the substrate by coextruding a color shifting material comprising a plurality
7 of multilayer optical interference flakes dispersed in a polymeric medium, with a material
8 forming the substrate.
9

10 7. The method of claim 1, further comprising the steps of forming a release layer on
11 the substrate, and of hot stamping the security article to an object.
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26